

INTECH Instrumentos y Equipos C.A.

Av. Río Caura, Torre Humboldt, Ofic 04-04,
Caracas, Venezuela 1080
Tel: 58-212-9784430, 9784433, 977.7654, 977.6346
Fax: 58-212-977.3613
E-mail: sales@intech-ie.com
RIF J-30615033-1

Oferta # C-2026-0028

Fecha: 27/01/2026

Su referencia Correo

Facturar a:

C.A. RON SANTA TERESA

RIF: J-00032569-3

Dirección: Carretera Panamericana, Hacienda Sta.
Teresa. El Consejo. Edo. Aragua. ZP 2118.
Venezuela.

Telf.: 0244-4002564 / 0424-3056226

Attn.: Adays Colina

Correo: acolina@ronsantateresa.com

Despachar a:

C.A. RON SANTA TERESA

El Consejo, Edo. Aragua – Venezuela

Vendedor	Condiciones	Referencia	Destino	Términos Pago	Validez
N. Carricatti	DDP	C-2023-0085/PL C-2025-0361	ARA	Ver abajo	30 días

Item	Cant	Descripción	Unitario US\$	Total US\$
1	1	METAL TUBE VA FLOW METER MODEL 3809G WITH TRANSMITTER, BROOKS INSTRUMENTS PN 3809GAA10CFDB3H3C000 Tag: FT-3321 LineDescription MT3809G Stainless Meter LIQUID 270 - 2700 LPH REF P/N Base Model MT3809 SS Max Press@TMin 275 PSIG (19 BAR) Max Press@TMax 148 PSIG (10.2 BAR) CRN Province N/A Max Temp 572F (300C) Min Temp -325F (-198C) Accuracy 2% -Direct and %-Liquid Meter Material 316/316L SS Connection Size 1-in Connection Type 150# RF Flange Inlet Down Outlet Up O-Ring Material None Lay Length 250 mm Valve Type No Valve Valve Conn No Valve Tube Size 10-C 1.30/V Float 10-V-270 Float Material 316L SS Range 270 - 2700 LPH Ref Conditions N/A Primary Scale Direct Read Secondary Scale Percent Scale	\$9.101,00	\$9.101,00

		Scale Type White Face Metal Scale Fluid LIQUID Density 800 kg/m3 Viscosity 1 cP Operating Temp 80C Operating Press 3 barg Amb Temp Limit -20C to 70C Ind. Housing XP Stainless Electrical Conn 1/2" NPT-F Ind/Alarm/Xmtr Transmitter w\ Digital Display Approvals DIV 1-ZONE 1 XP-IIC-IECEX Remote Relay None Power Supply GP Power Supply, 20-70 V AC/DC Cert1 N/A Cert2 N/A Factor Tag Scale x 27 = Factor Tag2 LPH Liquid@800 kg/m3 1 cP Factor Tag3 Additional Services Certificate of Conformance Pressure Test Cert 3.1 ICC Hazardous Location Cert Stainless Steel Tags GP Power Supply, 20-70 V AC/DC TagNumber(s) FT-3321		
2	1	METAL TUBE VA FLOW METER MODEL 3809G WITH TRANSMITTER, BROOKS INSTRUMENTS PN 3809GAA13DFDB3H3C000 Tag: FT-3224 LineDescription MT3809G Stainless Meter LIQUID 2200 - 20000 LPH REF P/N Base Model MT3809 SS Max Press@TMin 275 PSIG (19 BAR) Max Press@TMax 148 PSIG (10.2 BAR) CRN Province N/A Max Temp 572F (300C) Min Temp -325F (-198C) Accuracy 2% -Direct and %-Liquid Meter Material 316/316L SS Connection Size 2-in Connection Type 150# RF Flange Inlet Down Outlet Up O-Ring Material None Lay Length 250 mm Valve Type No Valve Valve Conn No Valve Tube Size 13-D 1.35/S Float 13-S-925 Float Material 316L SS	\$10.837,00	\$10.837,00

		Range 2200 - 20000 LPH Ref Conditions N/A Primary Scale Direct Read Secondary Scale Percent Scale Scale Type White Face Metal Scale Fluid LIQUID Density 970 kg/m3 Viscosity 1 cP Operating Temp 100C Operating Press 3 barg Amb Temp Limit -20C to 70C Ind. Housing XP Stainless Electrical Conn 1/2" NPT-F Ind/Alarm/Xmtr Transmitter w\ Digital Display Approvals DIV 1-ZONE 1 XP-IIC-IECEX Remote Relay None Power Supply GP Power Supply, 20-70 V AC/DC Cert1 N/A Cert2 N/A Factor Tag Scale x 200 = Factor Tag2 LPH Liquid@970 kg/m3 1 cP Factor Tag3 Additional Services Certificate of Conformance Pressure Test Cert 3.1 ICC Hazardous Location Cert Stainless Steel Tags GP Power Supply, 20-70 V AC/DC TagNumber(s) FT-3224		
3	1	METAL TUBE VA FLOW METER MODEL 3809G WITH TRANSMITTER, BROOKS INSTRUMENTS PN 3809GBA07DFDB3H3C000 Tag: FT-3313 LineDescription MT3809G Stainless Meter C2H6O 23 - 230 LPH REF P/N Base Model MT3809 SS Max Press@TMin 275 PSIG (19 BAR) Max Press@TMax 148 PSIG (10.2 BAR) CRN Province N/A Max Temp 572F (300C) Min Temp -325F (-198C) Accuracy 2% -Direct and %-Liquid Meter Material 316/316L SS w\Cert 3.1-Material Connection Size 1/2-in Connection Type 150# WNRF Flange Inlet Down Outlet Up O-Ring Material None Lay Length 250 mm Valve Type No Valve	\$9.268,00	\$9.268,00

		Valve Conn No Valve Tube Size 7-D 1.2/S Float 7-S-16 Float Material 316L SS Range 23 - 230 LPH Ref Conditions N/A Primary Scale Direct Read Secondary Scale Percent Scale Scale Type White Face Metal Scale Fluid C2H6O Density 772.136 kg/m3 Viscosity 0.815 cP Operating Temp 40C Operating Press 9 psig Amb Temp Limit -20C to 70C Ind. Housing XP Stainless Electrical Conn 1/2" NPT-F Ind/Alarm/Xmtr Transmitter w\ Digital Display Approvals DIV 1-ZONE 1 XP-IIC-IECEX CSA Remote Relay None Power Supply GP Power Supply, 20-70 V AC/DC Cert1 N/A Cert2 N/A Factor Tag Scale x 2.3 = Factor Tag2 LPH C2H6O@ 772.136 kg/m3 0.815 cP Factor Tag3 Additional Services Decl 2.1 - Compliance (CoC) Cert 3.1 - Pressure Test Cert 3.1 - Material Cert 3.1 - International Calibration (ICC) Hazardous Location Cert Stainless Steel Tags GP Power Supply, 20-70 V AC/DC TagNumber(s) FT-3313		
4	1	METAL TUBE VA FLOW METER MODEL 3809G WITH TRANSMITTER, BROOKS INSTRUMENTS PN 3809GBA08BFDB3H3C000 Tag: FT-3323 LineDescription MT3809G Stainless Meter C2H6O 47 - 470 LPH REF P/N Base Model MT3809 SS Max Press@TMin 275 PSIG (19 BAR) Max Press@TMax 148 PSIG (10.2 BAR) CRN Province N/A Max Temp 572F (300C) Min Temp -325F (-198C) Accuracy 2% -Direct and %-Liquid Meter Material 316/316L SS w\Cert 3.1-Material	\$9.268,00	\$9.268,00

		Connection Size 1/2-in Connection Type 150# WNRF Flange Inlet Down Outlet Up O-Ring Material None Lay Length 250 mm Valve Type No Valve Valve Conn No Valve Tube Size 8-B 1.14/S Float 8-S-64 Float Material 316L SS Range 47 - 470 LPH Ref Conditions N/A Primary Scale Direct Read Secondary Scale Percent Scale Scale Type White Face Metal Scale Fluid C2H6O Density 734.7717 kg/m3 Viscosity 0.4269 cP Operating Temp 80C Operating Press 12 psig Amb Temp Limit -20C to 70C Ind. Housing XP Stainless Electrical Conn 1/2" NPT-F Ind/Alarm/Xmtr Transmitter w\ Digital Display Approvals DIV 1-ZONE 1 XP-IIC-IECEXCSA Remote Relay None Power Supply GP Power Supply, 20-70 V AC/DC Cert1 N/A Cert2 N/A Factor Tag Scale x 4.7 = Factor Tag2 LPH C2H6O@ 734.7717 kg/m3 0.4269 cP Factor Tag3 Additional Services Decl 2.1 - Compliance (CoC) Cert 3.1 - Pressure Test Cert 3.1 - Material Cert 3.1 - International Calibration (ICC) Hazardous Location Cert Stainless Steel Tags GP Power Supply, 20-70 V AC/DC TagNumber(s) FT-3323		
5	1	METAL TUBE VA FLOW METER MODEL 3809G WITH TRANSMITTER, BROOKS INSTRUMENTS PN 3809GBA08BFDB3H3C000 Tag: FT-3413 LineDescription MT3809G Stainless Meter C2H6O 46 - 460 LPH REF P/N Base Model MT3809 SS	\$9.268,00	\$9.268,00

	Max Press@TMin 275 PSIG (19 BAR) Max Press@TMax 148 PSIG (10.2 BAR) CRN Province N/A Max Temp 572F (300C) Min Temp -325F (-198C) Accuracy 2% -Direct and %-Liquid Meter Material 316/316L SS w\Cert 3.1-Material Connection Size 1/2-in Connection Type 150# WNRF Flange Inlet Down Outlet Up O-Ring Material None Lay Length 250 mm Valve Type No Valve Valve Conn No Valve Tube Size 8-B 1.14/S Float 8-S-64 Float Material 316L SS Range 46 - 460 LPH Ref Conditions N/A Primary Scale Direct Read Secondary Scale Percent Scale Scale Type White Face Metal Scale Fluid C2H6O Density 772.136 kg/m3 Viscosity 0.815 cP Operating Temp 40C Operating Press 9 psig Amb Temp Limit -20C to 70C Ind. Housing XP Stainless Electrical Conn 1/2" NPT-F Ind/Alarm/Xmtr Transmitter w\ Digital Display Approvals DIV 1-ZONE 1 XP-IIC-IECEXCSA Remote Relay None Power Supply GP Power Supply, 20-70 V AC/DC Cert1 N/A Cert2 N/A Factor Tag Scale x 4.6 = Factor Tag2 LPH C2H6O@ 772.136 kg/m3 0.815 cP Factor Tag3 Additional Services Decl 2.1 - Compliance (CoC) Cert 3.1 - Pressure Test Cert 3.1 - Material Cert 3.1 - International Calibration (ICC) Hazardous Location Cert Stainless Steel Tags GP Power Supply, 20-70 V AC/DC TagNumber(s) FT-3413		
--	--	--	--

6	1	METAL TUBE VA FLOW METER MODEL 3809G WITH TRANSMITTER, BROOKS INSTRUMENTS PN 3809GBA08BFFB3H3C000 Tag: FT-3414 LineDescription MT3809G Stainless Meter LIQUID 21 - 210 LPH REF P/N Base Model MT3809 SS Max Press@TMin 275 PSIG (19 BAR) Max Press@TMax 148 PSIG (10.2 BAR) CRN Province N/A Max Temp 572F (300C) Min Temp -325F (-198C) Accuracy 2% -Direct and % (VISC) Meter Material 316/316L SS w\Cert 3.1-Material Connection Size 1/2-in Connection Type 150# WNRF Flange Inlet Down Outlet Up O-Ring Material None Lay Length 250 mm Valve Type No Valve Valve Conn No Valve Tube Size 8-B 1.14/S Float 8-S-64 Float Material 316L SS Range 21 - 210 LPH Ref Conditions N/A Primary Scale Direct Read Secondary Scale Percent Scale Scale Type White Face Metal Scale Fluid LIQUID Density 870 kg/m3 Viscosity 20 cP Operating Temp 50C Operating Press 9 psig Amb Temp Limit -20C to 70C Ind. Housing XP Stainless Electrical Conn 1/2" NPT-F Ind/Alarm/Xmtr Transmitter w\ Digital Display Approvals DIV 1-ZONE 1 XP-IIC-IECEXCSA Remote Relay None Power Supply GP Power Supply, 20-70 V AC/DC Cert1 N/A Cert2 N/A Factor Tag Scale x 2.1 = Factor Tag2 LPH Liquid@870 kg/m3 20 cP Factor Tag3 Additional Services Decl 2.1 - Compliance (CoC) Cert 3.1 - Pressure Test Cert 3.1 - Material Cert 3.1 - International Calibration (ICC)	\$10.305,00	\$10.305,00
---	---	--	-------------	-------------

		Hazardous Location Cert Stainless Steel Tags GP Power Supply, 20-70 V AC/DC TagNumber(s) FT-3414		
7	1	METAL TUBE VA FLOW METER MODEL 3809G WITH TRANSMITTER, BROOKS INSTRUMENTS PN 3809GBA08BFFB3H3C000 Tag: FT-3415 LineDescription MT3809G Stainless Meter LIQUID 22 - 220 LPH REF P/N Base Model MT3809 SS Max Press@TMin 275 PSIG (19 BAR) Max Press@TMax 148 PSIG (10.2 BAR) CRN Province N/A Max Temp 572F (300C) Min Temp -325F (-198C) Accuracy 2% -Direct and % (VISC) Meter Material 316/316L SS w\Cert 3.1-Material Connection Size 1/2-in Connection Type 150# WNRF Flange Inlet Down Outlet Up O-Ring Material None Lay Length 250 mm Valve Type No Valve Valve Conn No Valve Tube Size 8-B 1.14/S Float 8-S-64 Float Material 316L SS Range 22 - 220 LPH Ref Conditions N/A Primary Scale Direct Read Secondary Scale Percent Scale Scale Type White Face Metal Scale Fluid LIQUID Density 830 kg/m3 Viscosity 20 cP Operating Temp 85C Operating Press 9 psig Amb Temp Limit -20C to 70C Ind. Housing XP Stainless Electrical Conn 1/2" NPT-F Ind/Alarm/Xmtr Transmitter w\ Digital Display Approvals DIV 1-ZONE 1 XP-IIC-IECEXCSEA Remote Relay None Power Supply GP Power Supply, 20-70 V AC/DC Cert1 N/A Cert2 N/A Factor Tag Scale x 2.2 = Factor Tag2 LPH Liquid@830 kg/m3 20 cP Factor Tag3	\$10.305,00	\$10.305,00

	Additional Services Decl 2.1 - Compliance (CoC) Cert 3.1 - Pressure Test Cert 3.1 - Material Cert 3.1 - International Calibration (ICC) Hazardous Location Cert Stainless Steel Tags GP Power Supply, 20-70 V AC/DC TagNumber(s) FT-3415		
	Tiempo de entrega Luego de recibir orden de compra y pago, Ítems 1,3-7: 9-12 semanas aprox. Item 2: 10-14 semanas aprox. Términos de pago Prepago con Orden de Compra Volumen y Peso Peso y volumen por avisar		

Subtotal	US\$	68.352,00
Flete	US\$	Incluido
Seguro	US\$	Incluido
IVA 16 %	US\$	10.936,32
IGTF	US\$	2.050,56
TOTAL	US\$	81,338.88

CONDICIONES DE PAGO
COMPONENTE IMPORTADO

1. *En DOLARES AMERICANOS (US\$) o en EUROS equivalentes mediante transferencia bancaria a cualquiera de las siguientes cuentas*

AMERANT BANK (in US\$)
220 ALHAMBRA CIRCLE, CORAL GABLES, FL. 33134
CUENTA NUMERO 8303790106
BENEFICIARIO INTECH INSTRUMENTOS Y EQUIPOS C.A.
ABA 067010509
SWIFT MNB MUS33

COMPONENTE NACIONAL

1. *En BOLIVARES (Bs.) mediante transferencia bancaria*

Banco Mercantil
Cuenta Corriente a nombre de INTECH Instrumentos y Equipos C.A.
– 0105-0011-73-1011-50499-5

	Condiciones de Venta
	<i>Todos los Equipos suministrados por INTECH Instrumentos y Equipos son Nuevos y cuentan con Certificados de Conformidad del Fabricante en caso de ser requeridos</i> <i>El Pedido Mínimo de Importación exclusiva es de US\$ 700.00 De ser menor la Orden será incluida en nuestro pedido ordinario mensual al proveedor por lo que habría que añadir 3-4 semanas adicionales al tiempo de entrega ofertado</i>
	Notas:
	<i>*El valor del material podrá ser pagado en US\$, EUR o en Bs previo acuerdo y aceptación entre ambas partes, y para este último el cálculo del mismo es tomado de acuerdo a lo informado por el Banco Central de Venezuela en su portal web www.bcv.org.ve y debe ser cancelado a la tasa oficial del día de pago</i> <i>*El valor del IVA podrá ser pagado y/o retenido en moneda local (Bs.) a la tasa referencial del día en caso de que el mismo no pueda ser pagado en US\$. El valor utilizado para el cálculo del mismo es tomado de acuerdo a lo informado por el Banco Central de Venezuela en su portal web www.bcv.org.ve y debe ser cancelado a la tasa oficial del día de pago</i>
	Aporte Social:
	No solicitado
	Garantía
	<i>Todos los materiales mantienen las condiciones de garantía Standard de los fabricantes.</i> <i>INTECH como representante y/o distribuidor exclusivo de múltiples marcas en el área de Instrumentación Industrial, calentamiento Eléctrico y Protección de sobrevoltajes, solo suministrara garantía y servicio a los equipos y materiales adquiridos a través de los canales de venta autorizados de INTECH tanto localmente como internacionalmente</i>
	Observaciones:
	<i>Pedido Mínimo US\$ 300.00</i> <i>En caso de Pedidos con Condiciones de Prepago, el Impuesto IVA puede ser cancelado a la entrega del material</i>