



Sales Quote

INDUSTRIAL BUSINESS INTL CORP

1580 Sawgrass Corporate Parkway

Suite 130, Sunrise, FL 33323

Tel: 954-302-3187, 315-4781

Fax: 954-838-7746

E-mail: ibicorp@intech-ie.com

Tax Certificate No. 16-8012998465-1

Quote #**IBI-2025-0147****Date:**Oct 6th, 2025**Customer ID****PETROPIAR - VEN****Bill To:****Chevron PetroPiar**

Complejo Petrolero y Petroquimico Jose, Edo

Anzoategui, Venezuela

Att: Hector Santaella – Ing. Costos

santaellahj@pdvsa.com**Ship To:**Custom Agent to be informed at La Guaira port,
Venezuela

Your #	Our #	Sales Rep	CIF	SHIP VIA	Terms	Validity
25-0491	IBI-2025-0147 / QUO00021703-1	L. Zuñiga	Maiquetia Airport, VEN	BWPPD	See below	60 days

Item	Qty	Units	Description	Unit Pr (US\$)	Total (US\$)
1	40	Pcs	WIKA PRESSURE GAUGES SERIES 23X.30 - Solid-front Safety Case Pressure Model: 233.30 Specifications according to data sheet: PM 02.04 Measuring System: Stainless Steel Case filling: with Nominal size: 2.5" Measuring range: gauge pressure range Scale range: 0/30 psi Process Connection: 1/2 NPT Connector location: lower mount Window: laminated safety glass Pointer: adjustable pointer Special design features: NACE Sour Gas Service Accuracy Class: +/- 2/1/2% (ASME B40.100 Grade A) Case surface: bare case / polished ring Material pressure element: Measuring System 316 SS Case filling fluid: Silicone, 1000 cSt Ingress Protection: IP 65 Permissible medium temperature: + 100 °C Permissible ambient temperature: -20 ... +60 °C Pressure Gauge Standard: US-Standard WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock QR code with extended serial number on dial Permissible ambient temperature: -20 ... +60 °C	355.00	14,200.00
2	60	Pcs	WIKA CAPSULE PROCESS PRESSURE GAUGE SERIES 6X2.34 Type 6X2.34 - Capsule Process Gauges Specifications according to data sheet: PM 06.07 Case: Black Plastic Bezel ring: Threaded Retainer Ring, Plastic, Black Accuracy Class: +/- 2/1/2% (ASME B40.100 Grade A) Measuring System: Stainless Steel Case filling: without	1,025.00	61,500.00

			Nominal size: 4.5" Unit: inH2O Scale range: 0 inH2O...150 inH2O Process Connection: 1/2 NPT Connector location: lower mount Special Design Features: NACE Sour Gas Service Movement: stainless steel Package: Single packing Window: laminated safety glass Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock QR code with extended serial number on dial additional mark for special design: *NACE* *SOUR GAS SERVICE* imprint material on dial: *316 SS wetted parts* inner packages label: Wika USA outside packages label: Wika USA		
3	30	Pcs	WIKA PRESSURE GAUGES SERIES 23X.30 - Solid-front Safety Case Pressure with DIAPHRAGM SEAL Process gauge Model: 233.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: with Nominal size: 4.5" Scale range: -30 inHg/30 psi Process Connection: Diaphragm Seal Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Special design features: NACE Sour Gas Service Accuracy Class: +/- 0.5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: Silicone, 1000 cSt Ingress Protection: IP 65 Dial description: WIKA Dial background: Reflective Fluorescent Yellow *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock QR code with extended serial number on dial Diaphragm seal system with 1 diaphragm seal Assembly specification High-Side: Direct assembly System fill fluid: KN 2 Silicone oil for general applications Process temperature min.: + 21°C (room temperature) Process temperature max.: + 40°C Ambient temperature pressure meas. min: + 10°C Ambient temperature pressure meas. max: + 40°C Diaphragm seal with threaded process connection Specifications according to data sheet: ACS 99.01	1,850.00	55,500.00

			Specifications according to data sheet: ACS 99.03 Specifications according to data sheet: in preparation (Typ 990.14) Diaphragm seal: Model 990.10 Threaded connection: 1/2" NPT female Flushing connection: 1 x 1/4 NPT female Nominal pressure rating: 1500 PSI Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4404 (316L); UNS S31603 Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Gasket: FPM max. 200°C Fastening parts: Retainer flange and bolts in stainless steel Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603)		
4	1,000	Pcs	WIKA PRESSURE GAUGES SERIES 23X.30 - Solid-front Safety Case Pressure with DIAPHRAGM SEAL Process Gauge Model: 232.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: without Nominal size: 4.5" Scale range: 0/600 psi Process Connection: Diaphragm Seal Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Special design features: NACE Sour Gas Service Accuracy Class: +/- 0.5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: prepared for filling Ingress Protection: IP 65 Dial description: WIKA Dial background: Reflective Fluorescent Yellow *WIKA®* CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock QR code with extended serial number on dial Diaphragm seal system with 1 diaphragm seal Assembly specification High-Side: Direct assembly System fill fluid: KN 2 Silicone oil for general applications Process temperature min.: + 21°C (room temperature) Process temperature max.: + 40°C Ambient temperature pressure meas. min: + 10°C Ambient temperature pressure meas. max: + 40°C Diaphragm seal with threaded process connection Specifications according to data sheet: ACS 99.01 Specifications according to data sheet: ACS 99.03 Specifications according to data sheet: in preparation (Typ 990.14) Diaphragm seal: Model 990.10 Threaded connection: 3/4" NPT female Nominal pressure rating: 1500 PSI Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4404 (316L); UNS S31603	1,570.00	1,570,000.00

			Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Gasket: FPM max. 200°C Fastening parts: Retainer flange and bolts in stainless steel Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603)		
5	100	Pcs	WIKA DIFFERENTIAL PRESSURE GAUGES SERIES 73X with DIAPHRAGM SEAL Process Gauge Model: 732.51 Specifications according to data sheet: APM 732.51 (APM 07.05) Case: stainless steel Bezel ring: stainless steel Movement: stainless steel Case filling: without Nominal size: 4" Scale range: 0/30 psid Process Connection: Diaphragm Seal Connector location: lower mount Special design features: NACE MR 0175 / ISO 15156-3 Accuracy Class: class 1.6 Maximum Static Pressure: 25 bar Overpressure Safety: 20 bar Ingress Protection: IP 54 Pointer: adjustable pointer Window: laminated safety glass Pressure Gauge Standard: International (standard Europe) CHEVRON Logo (2 colors) serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock QR code with extended serial number on dial case: with pressure blowout disk Diaphragm seal system with 2 diaphragm seals Assembly specification High-Side: Direct assembly Height difference high side: no height difference Assembly specification Low-Side: 2 meter capillary; stainless-steel System fill fluid: KN 2 Silicone oil for general applications Height difference low side: no height difference Process temperature min.: - 10°C Process temperature max.: + 200°C Ambient temperature pressure meas. min: + 10°C Ambient temperature pressure meas. max: + 40°C diameter of capillary: ID 2mm (3x0.5 mm) Version according to NACE: Version according to NACE MR 0175 according to Technical Information IN 00.21 Diaphragm seal with threaded process connection Specifications according to data sheet: ACS 99.01 Specifications according to data sheet: ACS 99.03 Specifications according to data sheet: in preparation (Typ 990.14) High-/Low-Side: High-Side Diaphragm seal: Model 990.40 Threaded connection: 3/4" NPT female Nominal pressure rating: 200 PSI Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4404 (316L); UNS S31603 Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Gasket: FPM max. 200°C Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Diaphragm seal with threaded process connection Specifications according to data sheet: ACS 99.01 Specifications according to data sheet: ACS 99.03	6,990.00	699,000.00



			Specifications according to data sheet: in preparation (Typ 990.14) High-/Low-Side: Low-Side Diaphragm seal: Model 990.40 Threaded connection: 3/4" NPT female Nominal pressure rating: 200 PSI Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4404 (316L); UNS S31603 Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Gasket: FPM max. 200°C Fastening parts: Without												
			Delivery Time Item 1, 3, 4: 14-15 Weeks ARO and Payment 1st Milestone Item 2, 5: 22 Weeks ARO and Payment 1st Milestone Partial Shipments allowed (WIKA) Payment Terms • 50% with your Order • Balance Net 30 days delivery time DDP Volume & Weight (to be reconfirmed) To be advised – Aprox 9,000 Lbs General Warranty: WIKA warrants its products to be free from defects in material and/or workmanship for a period of eighteen (18) months following shipment or twelve (12) months following start up, whichever occurs first, provided that written claim be made during the period of the warranty. Manufacturer's obligation under this warranty is limited solely to repairing or replacing necessary parts and in no event shall Manufacturer's be liable for damages in excess of the amount paid by the purchaser. Project Cancellation charges: <table><tr><td>15%</td><td>Up to submittal of Engineering & Design Drawings and Documents</td></tr><tr><td>25%</td><td>After submittal of Engineering & Design Drawings and Documents</td></tr><tr><td>50%</td><td>After material order placement and before production commences</td></tr><tr><td>75%</td><td>Within two weeks of production release</td></tr><tr><td>100%</td><td>Two weeks after production commences</td></tr></table> Cci: W. Brito – INTECH PLCRZ	15%	Up to submittal of Engineering & Design Drawings and Documents	25%	After submittal of Engineering & Design Drawings and Documents	50%	After material order placement and before production commences	75%	Within two weeks of production release	100%	Two weeks after production commences		
15%	Up to submittal of Engineering & Design Drawings and Documents														
25%	After submittal of Engineering & Design Drawings and Documents														
50%	After material order placement and before production commences														
75%	Within two weeks of production release														
100%	Two weeks after production commences														



**PLEASE TRANSFER TO OUR
ACCOUNT AT:**

TRUIST Bank.
450 North Pine Island
Plantation, FL 33324
Account #: 0140953040
ABA# 053-101-121
Routing/Transit Number: 2631-9138-7
Swift Code: BRBTUS33

THANK YOU FOR YOUR BUSINESS

Subtotal	US \$	2,400,200.00
Freight	US \$	Included
Insurance	US \$	Included
Docs.	US \$	Included
TOTAL	US \$	2,400,200.00