



Sales Quote

INDUSTRIAL BUSINESS INTL CORP

1580 Sawgrass Corporate Parkway
Suite 130, Sunrise, FL 33323
Tel: 954-315-4781
Fax: 954-838-7746
E-mail: ibicorp@intech-ie.com

Quote #**IBI-2024-0051****Date:****May 17th, 2024****Customer ID****CHEVRON PETROPIAR****Bill To:****PDVSA PETROPIAR**

Att: Nancy Cordero / Denismar Zabala
T: 0281-2802417 / 0416-5821592
Gerencia Ingeniera de Costos
Correo: corderonj@petropiar.pdvsa.com
zabaladh@petropiar.pdvsa.com

Ship To:**CHEVRON PETROPIAR Warehouse**

Your #	Our #	Sales Rep	Incoterms - CPT	SHIP VIA	Terms	Validity
Email 24-0384	IBI-2024-0051/RFQ- 202405-01-WIDN- QUO00016623-1	L. Zuñiga N. C.	Pto La Cruz, Venezuela	BWPPD	100% Prepayment	30 days

Item	Qty	Units	Description	Unit Pr (US\$)	Total (US\$)
1	226	Pc	Pressure Gauge Range 0-300 PSIG, dial 4 ½ " Thermoplastic case with filler, WIKA PN 80050430 Process Gauge Model: 232.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: without Nominal size: 4.5" Scale range: 0/300 psi 2nd Scale / Special Scale: 2nd scale bar Process Connection: 1/2 NPT Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: prepared for filling Ingress Protection: IP 65 Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black color for 2.scale (inside): red dial background: White *WIKA®* serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock Logo: CHEVRON (2 colores)	\$350,00	\$79.100,00
2	42	Pc	ASSEMBLY Pressure Gauge with diaphragm and cooling element, Range 0-600 PSIG, dial 4 ½ ", WIKA INSTRUMENTS PN 80066219 Process Gauge Model: 233.34 Specifications according to data sheet: APM 02.10	\$1.900,00	\$79.800,00

			Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: with Nominal size: 4.5" Scale range: 0/600 psi Process Connection: Diaphragm Seal Connector location: lower mount Window: laminated safety glass Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: Glycerine Ingress Protection: IP 65 Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKA®* serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock Diaphragm seal system with 1 diaphragm seal Assembly specification High-Side: Direct assembly System fill fluid: KN 2 Silicone oil for general applications Process temperature min.: + 21°C (room temperature) Process temperature max.: + 100°C Ambient temperature pressure meas. min: + 10°C Ambient temperature pressure meas. max: + 40°C Diaphragm seal with threaded process connection Specifications according to data sheet: ACS 99.01 Specifications according to data sheet: ACS 99.03 Specifications according to data sheet: in preparation (Typ 990.14) Diaphragm seal: Model 990.10 Threaded connection: 3/4" NPT female Nominal pressure rating: PN 100 Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603 Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Gasket: FPM max. 200°C Fastening parts: Retainer flange and bolts in stainless steel Label: WIKA standard without / with Tag-number Logo: CHEVRON (2 colores)		
3	42	Pc	Pressure Gauge Range 0-1500 PSIG, dial 4 ½ " Thermoplastic case with filler, WIKA PN 80066220 Process Gauge Model: 233.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: with Nominal size: 4.5" Scale range: 0/1500 psi 2nd Scale / Special Scale: 2nd scale bar Process Connection: 1/2 NPT Connector location: lower mount Window: laminated safety glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L	\$480,00	\$20.160,00

			Case filling fluid: Silicone, 1000 cSt Ingress Protection: IP 65 Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black color for 2.scale (inside): red dial background: White *WIKA®* serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock Logo: CHEVRON (2 colores)		
4	44	PC	ASSEMBLY Bimetal Thermometer, Range 0 °F ... 250 °F, dial 5 " with Thermowell Tapered, WIKA INSTRUMENTS PN 80066221-52898339 Bimetal thermometer, Process grade according to ASME B40.200 Model: TG53.5Z Specifications according to data sheet: ATM 53.02 Accuracy Class: +/- 1% of Full Scale (ASME B40.3) Nominal size: 5" Connector position: back mount, adjustable Design of Connection: standard, male thread Process Connection: 1/2" NPT Scale Range: 0 °F ... 250 °F Stem Diameter: 1/4" Insertion length L1: 10,0 Window: Flat Instrument Glass Ingress Protection: IP 66 / NEMA 4X Permissible ambient temperature: -40 ... +100 °C with Serial number Manufacturer logo: *WIKA®* Logo: CHEVRON (2 colores) Threaded Thermowell TW15, solid machined Specifications according to data sheet: TW 95.15 Head Design: Hexagon Thermowell Style: Tapered Unit of Measure: Imperial (inch) Process thread [P or E]: 1/2" NPT Instrument connection [N]: 1/2 NPT female Insertion length [U]: 9,000 inch Head Length: 1.75" Bar Material: Stainless steel 316/316L Bore size [B or d1]: 0.260 inch (6.6 mm) Root diameter [Q]: 0.625 inch Tip diameter [V or F3]: 0.500 inch Bore depth / stem length (US): 10,500 inch Tip thickness [Tt]: 0.250 inch (6.4 mm)	\$1.090,00	\$47.960,00
			Delivery Time Items 1, 3, 5: 8 – 10 Weeks ARO and Payment Item 2, 4: 14 – 16 Weeks ARO and Payment Payment Terms • 100% Prepayment with Order Packing Material will be Securely packed in wooden crates suitable for air freight and export. Volume & Weight To be advised General Warranty: WIKA warrants its products to be free from defects in material and/or workmanship for a period of eighteen (18) months following shipment or twelve		

**INDUSTRIAL BUSINESS INTL CORP**

1580 Sawgrass Corporate Parkway

Suite 130, Sunrise, FL 33323

Tel: 954-315-4781

Fax: 954-838-7746

E-mail: ibicorp@intech-ie.com

			(12) months following start up, whichever occurs first, provided that written claim be made during the period of the warranty. Manufacturer's obligation under this warranty is limited solely to repairing or replacing necessary parts and in no event shall Manufacturer's be liable for damages in excess of the amount paid by the purchaser.		
--	--	--	---	--	--

**PLEASE TRANSFER TO OUR
ACCOUNT AT:**

TRUIST BANK.

450 North Pine Island

Plantation, FL 33324

Account #: 0140953040

ABA# 053-101-121

Routing/Transit Number: 2631-9138-7

Swift Code: BRBTUS33

Subtotal	US\$	227,020.00
Freight	US\$	-
Insurance	US\$	-
Docs.	US\$	-
TOTAL	US\$	227,020.00

THANK YOU FOR YOUR BUSINESS