



Sales Quote

INDUSTRIAL BUSINESS INTL CORP

1580 Sawgrass Corporate Parkway

Suite 130, Sunrise, FL 33323

Tel: 954-302-3187, 315-4781

Fax: 954-838-7746

E-mail: ibicorp@intech-ie.com

Tax Certificate No. 16-8012998465-1

Quote #

IBI-2024-0070

Date:

Aug 07th, 2024

Customer ID

CATHEQUIM**Bill To:****CATHEQUIM, C.A****RIF: J-29847205-7**Dirección: Av. Sorte, hombrillo norte, Local Galpón
Cathequim S/N Zona Industrial de Chivacoa.

Telf: 0414-5035661

Attn: Luishana Dudamell

Correo: gerenciaid@cathequim.com

Ship To:El material se enviará al almacén/broker del
cliente en Venezuela.

Your #	Our #	Sales Rep	Incoterms – DDP	SHIP VIA	Terms	Validity
Budgetary	IBI-2024-0070/PL	N. Carricatti	Yaracuy	Pick up	Ver abajo	60 days

Item	Qty	Units	Description	Unit Pr (US\$)	Total (US\$)
UNIDAD SPRAY DRYING					
1	1	Pc	MINI SPRAY DRYER S-300 ADVANCED 220C Pro, 220V, BUCHI PN 11S300A110100 The Mini Spray Dryer S-300 with its modern user interface offers the highest flexibility in laboratory spray drying. Features are: Particle size range: 1 - 25 micrometers Yields: up to 70% Collector type: Cyclone Nozzle type: Two fluid, three fluid or ultrasonic nozzle User interphase: 7" touch screen Instrument Type: Sample types: water and organic solvents based Temperature: Maximum inlet temperature: 220°C Pro: Auto and method mode: yes Note: it is required a dry air supply 50 L/min+, 6-8 bar pressure (oil-free air compressor)	77,370.00	77,370.00
2	1	--	DESCUENTO ESPECIAL 10% POR COMPRA DE S-300 ADVANCED PN PROMSET3 Nota: solamente valido por 2024	-7,737.00	-7,737.00
3	1	Pc	MODULO DESHUMIDIFICADOR S-396, 220V / 50-60 Hz, BUCHI PN 11074006 Providing stable spray drying conditions The Dehumidifier S-396 is designed to provide dry air or to enable continuous work with water and organic solvent mixtures for the Mini Spray Dryer S-300. The accessory improves your spray drying performance, while providing stable spray drying conditions.	17,666.00	17,666.00

			Cooling temperature: 0°C Collection volume: 1 L of water		
			UNIDAD ENCAPSULADOR		
4	1	Pc	ENCAPSULATOR B-390, 100 - 240 V / 50 - 60 Hz WITH CONCENTRIC NOZZLE SET, BUCHI PN 11058210-11058051 The Encapsulator B-390 is a versatile system for encapsulation of active ingredients and materials for R&D purposes. From pharma to food samples, the adaptability of the device lets you obtain innovative microbeads and microcapsules. Capsule type: matrix beads or core shell capsules Final particle size: 150 >¼ ± ¼ m - 4 mm Productivity: 1 - 40 mL / min Operation mode: Open mode Nozzle set for capsule production. Pulsation chamber shell vibrated plus a set of 7 external nozzles with high precision opening of 0.2, 0.3, 0.4, 0.5, 0.6, 0.7 and 0.9 mm made of stainless steel, incl. 1000 mL pressure bottle. Note: it is required a dry air supply 1 L/min+, 1.5-2 bar pressure (oil-free air compressor)	62,444.00	62,444.00
5	1	Pc	DRY AIR SUPPLY FOR THE ENCAPSULATOR, 220V / 50-60 Hz, BUCHI PN 11070538 Dry Air Supply for the Encapsulator The easy way to deliver compressed air	5,234.00	5,234.00
6	1	Pc	PRESSURE BOTTLE 1000 ML COMPLETE (SPARE PART), BUCHI PN 11058191 Pressure bottle 1000 mL complete Glass bottles with fittings, tubes and air filter, working pressure up to 1.5 bar, autoclavable	1,193.00	1,193.00
			UNIDAD DESTILADORA/DIGESTORA		
7	1	Set	SISTEMA DESTILADOR DIST LINE MODELO MULTI DIST, BUCHI PN 11K36532210 MultiDist with glass splash protector, titration setup, external titrator, 220-240V ± 10%, 50/60 Hz. The distillation unit MultiDist allows an automatic and quantitative steam distillation of steam volatile analytes including nitrogen. It is equipped with the AutoDist mode, an acid resistant, NaOH-resistant, H2O and boric acid dosing pumps and a 7.0" color touch display with a control wheel. Complete and ready to use, supplied with Peristaltic pump for sample aspiration : Yes Interface : I-300 Pro Splash protector : Glass	47,982.00	47,982.00

			Titration setup & peristaltic pump for receiving vessel in order to connect a titrator : Yes External titrator Metrohm Eco Titrator : Yes Cooling water supply: none Includes: SENSOR DE DETECCIÓN DE REACCION, BUCHI PN 11072666 3 x JUEGO DE SENSOR DE NIVEL DE TANQUE, BUCHI PN 11072294 SENSOR DE NIVEL. BUCHI PN 11070270 LUZ DE ESTADO, BUCHI PN 11068959 JUEGO DE TUBOS DE MUESTRA DE 300 ML. BUCHI PN 11059690		
8	1	Pc	SPEEDDIGESTER K-439, BUCHI PN 1154392200 Büchi SpeedDigerster K-439 with condensate trap 220-240V +/-10%, 50/60 Hz Programmable IR-digestion system for twelve 300ml sample tubes with two tight suction modules with condensate trap and adjustable heating level from 70°C to 580°C. The software allows to enter exact temperature values and digestion time, Visualization of digestion process through graphical display, Storage of 50 digestion methods, including 20 Büchi standard methods, Robust design with metal components made from acid-resistant stainless steel. Complete and ready to use, supplied with 2 suction modules with condensate trap 12 sample tubes (300ml), 2 racks for 6 sample tubes. For exhaust and neutralization of the acid fumes generated during digestion the use of a Scrubber K-415 is recommended.	19,102.00	19,102.00
9	1	Pc	RECIRCULATION CHILLER F-314, BUCHI PN 11F31401K Recirculation chiller F-314 1400 W at 15°C, Display, 230 V Cooling capacity 1400 W at 15 °C for temperatures from -10 to 25 °C Incl. chiller connection kit, order code 11056900 for retrofitting of the F-314	14,872.00	14,872.00
10	1	Pc	SCRUBBER K-415 TRIPLESCRUB, BUCHI PN 114152330 Scrubber K-415 TripleScrub 230V +/-10%, 50/60Hz The K-415 TripleScrub is a three-step gas scrubbing instrument with a powerful pump and condensation, neutralization and adsorption steps. Aggressive acid or alkali fumes are sucked off by means of the integrated pump into the first stage (condenser) for precondensation to avoid dilution of the second stage (neutralization). The output from the condensation stage is neutralized in the neutralization vessel.	13,106.00	13,106.00



			A third stage (adsorption) then collects particles from organic or inorganic substances. To allow the user greater flexibility, the suction power of the Scrubber can be adjusted anytime. The K-415 can be controlled via a digester.		
11	1	--	DESCUENTO ESPECIAL GRATIS ITEM 10 POR COMPRA DE ITEM 7, 8 y 9. PN PROM1SET8 <i>Nota: solamente valido por 2024</i>	-13,106.00	-13,106.00
			Delivery Time Luego de recibir orden de compra y pago, Items: 6-12 semanas aprox. El tiempo de entrega de los elementos ofertados queda sujeto a cambios generados por eventos fuera de manejo de la compañía como: 1. Fenómenos climáticos que no permitan el transporte de materia prima a la fábrica, transporte local en el extranjero del material manufacturado y/o transporte internacional del producto. 2. Normal funcionamiento de aduana Venezolana y/o extranjeras. 3. Alteración del orden público en el país de origen, país en tránsito y/o país final. 4. Actos delictivos y/o terroristas. 5. Cualquier otro evento considerado de fuerza mayor. Payment terms 100 % con orden de compra Volume & Weight Peso item 1-3 – 135 kg + aprox. Peso item 4-6 – 20 kg + aprox. Peso item 7-11 – 130 kg + aprox.		

**PLEASE TRANSFER TO OUR
ACCOUNT AT:**

Branch Banking & Trust Co.

450 North Pine Island

Plantation, FL 33324

Account #: 0140953040

ABA# 053-101-121

Routing/Transit Number: 2631-9138-7

Swift Code: BRBTUS33

THANK YOU FOR YOUR BUSINESS

Subtotal	US \$	238,126.00
Freight	US \$	Included
Docs.	US \$	Included
TOTAL	US \$	238,126.00