



Sales Quote

INDUSTRIAL BUSINESS INTL CORP

1580 Sawgrass Corporate Parkway
Suite 130, Sunrise, FL 33323
Tel: 954-302-3187, 315-4781
Fax: 954-838-7746
E-mail: ibicorp@intech-ie.com
Tax Certificate No. **16-8012998465-1**

Quote #**IBI-2024-0082-1****Date:**Dec 05th, 2024**Customer ID****M&E SERVICES C.A.****Bill To:****M&E SERVICES C.A.****RIF: J-40995443-9**

Av. Country Club, Edificio Caribbean country, Piso 4,
Local E7, Urbanizacion Urdaneta, Barcelona
Anzoategui, Zona Postal 6001

Telf: 0281-2748153 / 0424-8836289

Attn: Ing. Carlos Puerta

Correo: info@myeservicesca.comprocuramyervices@gmail.com**Ship To:**

The material will be sent to the customer's
warehouse / broker in Venezuela

Your #	Our #	Sales Rep	Incoterms - DDP	SHIP VIA	Terms	Validity
Email	IBI-2024-0082-1/ WIDN-202411-02/ QUO00018702-1	N. Carricatti	VEN	Pick up	Ver abajo	30 days

Item	Qty	Units	Description	Unit Pr (US\$)	Total (US\$)
DISTILLATION UNIT (ASTM D86)					
1	50	Pc	PRESSURE GAUGE DIAL 4" 0/300 PSI MODEL 233.50, WIKA PN 80NG06CV93IN68 Type 23X.50 - SS Case - Pressure Gauges Series Model: 233.50 Specifications according to data sheet: PM 02.02 Measuring System: Stainless Steel Case filling: with Nominal size: 4" Scale range: 0/300 psi Process Connection: 1/2 NPT Connector location: lower mount Window: Polycarbonate Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: glycerine-water-mixture Ingress Protection: IP 65 Permissible medium temperature: + 100 °C Permissible ambient temperature: -20 ... +60 °C Pressure Gauge Standard: US-Standard Manufacturer logo: *WIKA®* with Serial number QR code with extended serial number on dial	\$146,00	\$7.300,00
2	200	Pc	PRESSURE GAUGE DIAL 4.5" 0/1000 PSI MODEL 233.34, WIKA PN 52NG95CV44IN84 Process Gauge	\$191,00	\$38.200,00

			Model: 233.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: with Nominal size: 4.5" Scale range: 0/1000 psi Process Connection: 1/2 NPT Connector location: lower mount Window: acrylic (PMMA) Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: Glycerine Ingress Protection: IP 65 Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKA®* serial number on dial: Serial number *...* stop pin on dial: at 6 o'clock		
3	40	Pc	PRESSURE GAUGE DIAL 6" 0/2000 PSI MODEL 232.50, WIKA PN 80NG06CV93IN71 Type 23X.50 - SS Case - Pressure Gauges Series Model: 232.50 Specifications according to data sheet: PM 02.02 Measuring System: Stainless Steel Case filling: without Nominal size: 6" Scale range: 0/2000 psi Process Connection: 1/2 NPT Connector location: lower mount Window: Flat Instrument Glass Pointer: standard pointer Accuracy Class: class 1.0 Material pressure element: Measuring System 316L Ingress Protection: IP 65 Permissible medium temperature: + 200 °C Permissible ambient temperature: -40 ... +60 °C Pressure Gauge Standard: International (standard Europe) Manufacturer logo: *WIKA* with Serial number QR code with extended serial number on dial	\$211,00	\$8.440,00
4	400	Pc	PRESSURE GAUGE DIAL 4.5" 0/600 PSI MODEL 233.34, WIKA PN 80NG06CV93IN73 Process Gauge Model: 233.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel	\$184,00	\$73.600,00

			Case filling: with Nominal size: 4.5" Scale range: 0/600 psi Process Connection: 1/2 NPT Connector location: lower mount Window: Flat Instrument Glass Restrictor: stainless steel, D 0.6 Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: Glycerine Ingress Protection: IP 65 Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKAR* serial number on dial: Serial number *...* QR code with extended serial number on dial stop pin on dial: at 6 o'clock		
5	200	Pc	PRESSURE GAUGE DIAL 4.5" 0/300 PSI MODEL 233.34 WITH SEAL 990.10, WIKAR PN 80NG06CV93IN74 Process Gauge Model: 233.34 Specifications according to data sheet: APM 02.10 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: with Nominal size: 4.5" Scale range: 0/300 psi Process Connection: Diaphragm Seal Connector location: lower mount Window: Flat Instrument Glass Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: Glycerine Ingress Protection: IP 65 Dial description: Pressure Gauge Standard: US-Standard color for 1.scale (outside): black dial background: White *WIKAR* serial number on dial: Serial number *...* QR code with extended serial number on dial stop pin on dial: at 6 o'clock Diaphragm seal system with 1 diaphragm seal Assembly specification High-Side: Direct assembly System fill fluid: KN 2 Silicone oil for general applications Process temperature min.: + 21°C (room temperature) Process temperature max.: + 21°C (room temperature) Ambient temperature pressure meas. min: + 10°C Ambient temperature pressure meas. max: + 40°C Diaphragm seal with threaded process connection Specifications according to data sheet: ACS 99.01 Specifications according to data sheet: ACS 99.03	\$1.607,00	\$321.400,00



		Specifications according to data sheet: in preparation (Typ 990.14) Diaphragm seal: Model 990.10 Threaded connection: 3/4" NPT female Flushing connection: 1 x 1/4 NPT female Nominal pressure rating: PN 100 Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603 Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Gasket: FPM max. 200°C Fastening parts: Retainer flange and bolts in stainless steel Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Label: WIKA standard without / with Tag-number		
		Delivery Time After receipt of order and payment, Items: 10-12 weeks approx. (subject to changes) The delivery time of the items offered is subject to changes generated by events outside the company's control, such as: 1. Climatic phenomena that do not allow the transport of raw material to the factory, local transport abroad of the manufactured material and/or international transport of the product. 2. Normal functioning of Venezuelan and/or foreign customs. 3. Disruption of public order in the country of origin, country of transit and/or final country. 4. Criminal and/or terrorist acts. 5. Any other event considered force majeure. Payment terms 100% Prepayment with your order Volume & Weight Weight and Volume to be advised		

**PLEASE TRANSFER TO OUR
ACCOUNT AT:**

Branch Banking & Trust Co.
450 North Pine Island
Plantation, FL 33324
Account #: 0140953040
ABA# 053-101-121
Routing/Transit Number: 2631-9138-7
Swift Code: BRBTUS33

THANK YOU FOR YOUR BUSINESS

Subtotal	US \$	448,940.00
Freight	US \$	Included
Insurance	US \$	Included
Docs.	US \$	Included
TOTAL	US \$	448,940.00