



Sales Quote

INDUSTRIAL BUSINESS INTL CORP

1580 Sawgrass Corporate Parkway
Suite 130, Sunrise, FL 33323
Tel: 954-302-3187, 315-4781
Fax: 954-838-7746
E-mail: ibicorp@intech-ie.com
Tax Certificate No. **16-8012998465-1**

Quote #**IBI-2024-0110****Date:**Nov 18th, 2024**Customer ID****GABYCLAU****Bill To:****GABYCLAU, C.A.****RIF: J-29816330-5**

Av. principal de Lechería, Centro Empresarial
Lechería, Piso 5, Oficina 502. Zona postal 6016
Lechería – Edo. Anzoátegui
Telf: +58 412 869-4503
Attn: Ing. Irving Betancourt
Correo: estim.costos@gabyclau.com

Ship To:

Material will be sent to customer's warehouse in
Lechería, Edo. Anzoátegui.

Your #	Our #	Sales Rep	Incoterms - DDP	SHIP VIA	Terms	Validity
Budgetary	IBI-2024-0110/PL	S. Méndez	ANZ	DDP	See below	30 days

Item	Qty	Units	Description	Unit Pr (US\$)	Total (US\$)
1	1	Pc	DIFFERENTIAL PRESSURE TRANSMITTER DPT-20 RANGE -3 TO 3 BAR WITH DIAPHRAGM SEAL 990.10 CONNECTION 1/2" NPT FEMALE, WIKA PN 80069003 Electrical approval: ATEX Ignition protection type: Ex d - explosion proof Zone: Zone 1 attached to zone 0 gas [II 1/2G, 2G Ex d IIC T6] Housing material: Stainless steel cast single chamber enclosure execution: compact / IP66/IP68 (0.2bar); NEMA 6P Output signal: 4...20 mA, 2-wire, HART Electrical connection: 1/2" NPT female conduit Maximal working pressure: 160 bar (16 MPa / 2400 psi) Pressure range: -3 ... +3 bar Diaphragm material: 316L Sealing (temperature range): FKM (-20 ... +85 °C) Accuracy: 0.1 % of span Mounting element: mounting bracket for wall or pipe mounting (max. 2"), stainless steel Filling of sensor: Silicone oil for regular applications (KN2) Operating modes: Pressure measurement Scaling unit DP-measurement: psi Lower scaling value DP: 0 psi Upper scaling value DP: 36,00 Damping [s]: 1 s (default setting) Output signal low level in %: 0% Output signal low level in %: 100% Assembly specification High-Side: 6 meter capillary; stainless steel System fill fluid: KN 2 Silicone oil for general applications Process temperature min.: + 21°C (room temperature) Process temperature max.: + 40°C diameter of capillary: ID 2mm (3x0.5 mm) Diaphragm seal: Model 990.10 Threaded connection: 1/2" NPT female Flushing connection: 1 x 1/4 NPT female Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603 Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Certificate type: Inspection certificate acc. to EN 10204 3.1	5,605.00	5,605.00

2	1	Pc	PRESSURE GAUGE RANGE -30 INHG TO 15 PSI MODEL 233.34 WITH DIAPHRAGM SEAL 990.10 CONNECTION 1" NPT FEMALE, WIKA PN 80069002 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: with Nominal size: 4.5" Scale range: -30 inHg/15 psi Process Connection: Diaphragm Seal Connector location: lower mount Window: laminated safety glass Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: Silicone, 1000 cSt Ingress Protection: IP 65 Process temperature min.: + 21°C (room temperature) Process temperature max.: + 70°C Diaphragm seal: Model 990.10 Threaded connection: 1" NPT female Flushing connection: 1 x 1/4 NPT female Nominal pressure rating: PN 100 Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603 Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Gasket: FPM max. 200°C Certificate type: Inspection certificate acc. to EN 10204 3.1	1,242.00	1,242.00
3	1	Pc	PRESSURE GAUGE RANGE 0 TO 1000 PSI MODEL 233.34 WITH DIAPHRAGM SEAL 990.10 CONNECTION 1" NPT FEMALE, WIKA PN 80069004 Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225) Measuring System: Stainless Steel Case filling: with Nominal size: 4.5" Scale range: 0/1000 psi Process Connection: Diaphragm Seal Connector location: lower mount Window: laminated safety glass Pointer: adjustable pointer Accuracy Class: +/- .5% (ASME B40.100 2A) Material pressure element: Measuring System 316L Case filling fluid: Silicone, 1000 cSt Ingress Protection: IP 65 Process temperature min.: + 21°C (room temperature) Process temperature max.: + 70°C Diaphragm seal: Model 990.10 Threaded connection: 1" NPT female Flushing connection: 1 x 1/4 NPT female Nominal pressure rating: PN 100 Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603 Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Gasket: FPM max. 200°C Certificate type: Inspection certificate acc. to EN 10204 3.1	1,628.00	1,628.00
4	1	Pc	Compact pressure switch, flameproof Enclosure Ex d Model PCA, WIKA PN 80069009 Repeatability of set point: ≤ 1% of end of setting range switch enclosure: stainless steel 316L Measuring elements and wetted parts: Diaphragm Inconel + O-Ring FPM 1xDPDT, silver contact 150 ... 600 psi, working range -15 ... 900 psi, proof pressure 1500 psi	1,922.00	1,922.00

			Set Point not defined process connection: Adaptor 1/2 NPT-F electrical connection: 1/2 -14 NPT-F standard direct or wall mounting, fixing bore on the case Certificates: quality certificates Ingress Protection: IP66 PCA4MG 150 ... 600 psi IECEX-ATEX Ex d		
5	1	Pc	Absolute pressure switch, Flameproof Enclosure Ex d Models APA and APA10, WIKA PN 80069010 Repeatability of set point: $\leq 1\%$ of span Model 3: APA Model of measuring Cell: H-For setting range 0.4, 0.6, 1.0 and 1.5 bar abs. electric contacts: 2 x SPDT or 1 x DPDT silver contact Unit: bar absolute setting range, working range, proof pressure: 0...1,5 bar abs., working range 0...1,5 bar abs., proof pressure 11 bar abs. set point definition: Set Point not defined process connection: Adaptor 1/2 NPT-F electrical connection: 1/2 -14 NPT-F Mounting: Enclosure with plate for wall or direct mounting Diaphragm Material: Diaphragm AISI 316, Process Connection AISI 316L, gasket NBR Certificates: quality certificates brand: WIKA Instruments Italia Ingress Protection: IP66 IECEX-ATEX Ex d	2,734.00	2,734.00
6	1	Pc	PRESSURE GAUGE RANGE 0 TO 2000 PSI MODEL 232.50 WITH DIAPHRAGM SEAL 990.10 CONNECTION 1" NPT FEMALE, WIKA PN 80069004 Measuring System: Stainless Steel Case filling: without Nominal size: 4" Scale range: 0/2000 psi Process Connection: Diaphragm Seal Connector location: lower mount Window: laminated safety glass Pointer: adjustable pointer Explosion protection: ATEX Ignition protection type: Ex h Zone: Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C ... T450 °C Db X) Accuracy Class: class 1.0 Material pressure element: Measuring System 316L Ingress Protection: IP 65 Assembly specification High-Side: 3 meter capillary; stainless steel System fill fluid: KN 2 Silicone oil for general applications Process temperature min.: + 21°C (room temperature) Process temperature max.: + 70°C Diaphragm seal: Model 990.10 Threaded connection: 1/2" NPT female Flushing connection: 1 x 1/4 NPT female Nominal pressure rating: PN 250 Upper housing material / housing material: Stainless steel 1.4404 (316L); UNS S31603 Diaphragm material: Stainless steel 1.4435 (316L); UNS S31603 Lower housing material: in (Stainless steel 1.4404 (316L); UNS S31603) Gasket: FPM max. 200°C Certificate type: Inspection certificate acc. to EN 10204 3.1	1,644.00	1,644.00

**INDUSTRIAL BUSINESS INTL CORP**

1580 Sawgrass Corporate Parkway
Suite 130, Sunrise, FL 33323
Tel: 954-302-3187, 315-4781
Fax: 954-838-7746
E-mail: ibicorp@intech-ie.com

		Delivery Time After receipt of order and payment (subject to changes) Item 1-3,6: 16-18 weeks Item 4-5: 11-13 weeks The delivery time of the items offered is subject to changes generated by events outside the company's control, such as: 1. Climatic phenomena that do not allow the transport of raw material to the factory, local transport abroad of the manufactured material and/or international transport of the product. 2. Normal functioning of Venezuelan and/or foreign customs. 3. Disruption of public order in the country of origin, country of transit and/or final country. 4. Criminal and/or terrorist acts. 5. Any other event considered major force. Payment terms Prepayment with PO Volume & Weight Weight / Volume to be advised		
--	--	--	--	--

**PLEASE TRANSFER TO OUR
ACCOUNT AT:**

Branch Banking & Trust Co.
450 North Pine Island
Plantation, FL 33324
Account #: 0140953040
ABA# 053-101-121
Routing/Transit Number: 2631-9138-7
Swift Code: BRBTUS33

THANK YOU FOR YOUR BUSINESS

Subtotal	US \$	14,775.00
Freight	US \$	Included
Insurance	US \$	Included
Docs.	US \$	Included
TOTAL	US \$	14,775.00