



Sales Quote

INDUSTRIAL BUSINESS INTL CORP

1580 Sawgrass Corporate Parkway

Suite 130, Sunrise, FL 33323

Tel: 954-302-3187, 315-4781

Fax: 954-838-7746

E-mail: ibicorp@intech-ie.com

Tax Certificate No. 16-8012998465-1

Quote #**IBI-2024-0115****Date:**Dec 4th, 2024**Customer ID****Bill To:****REPRESENTACIONES SAJ, C.A.****RIF: J-29715432-9**

Cr via a Payara local Centro I Torre A, Tocuyano

Sector Sistema de Riego Las Majaguas Tocuyano

(Centro I) Portuguesa zona postal 3302

telf.: 0212-5156031

Attn:

E-mail:

Ship To:Material will be sent to customer's warehouse at
Representaciones SAJ, Tocuyano - Portuguesa.

<i>Your #</i>	<i>Our #</i>	<i>Sales Rep</i>	<i>Incoterms - DDP</i>	<i>SHIP VIA</i>	<i>Terms</i>	<i>Validity</i>
Budgetary	IBI-2024-0115/PL	S. Méndez	POR	DDP	See below	30 days

<i>Item</i>	<i>Qty</i>	<i>Units</i>	<i>Description</i>	<i>Unit Pr (US\$)</i>	<i>Total (US\$)</i>
1	2	Pc	MODULAR POLARIMETER MCP 5300 SUCROMAT, ANTON PAAR PN 182512 The MCP 5X00 Sucromat is a high-quality saccharimeter for polarimetric sugar analyses. A sugar factory's reception laboratory as well as the quality laboratory needs to follow up highest possible accuracy to increase the profit. With built-in automatic identification of sample cells (ToolmasterTM), precise temperature measurement, automatic adjustment, live view of the sample cell (FillingCheckTM), and long-life LED light source. All Anton Paar digital saccharimeters comply with the official ICUMSA methods as well as further national and international standards (e.g. OIML and Australian standard K157). Other scales such as °Z International Sugar Scale (with and without temperature compensation, depending on application), %Sucrose, %Glucose, %Purity, and °Optical Rotation are integrated as standard. Include: -Pertier option (188427) -Air pump (159058) -Polarimeter tube stainless steel 200mm (104124) -Glass window 15.mm (49703) -Cleaning brush set (156597)	\$18.885,00	\$37.770,00
2	1	Pc	NO BID	-	-
3	1	Pc	NATURAL CONVECTION OVEN MODEL TCN 50 SUPER, ARGO LAB PN 41200502-41100102-41100152 Touch screen colour display. Programs, ramps, graph, alarm, User Management, Activity log. Unlimited data memory with USB port and USB stick. Include: Steel wire shelf for TCN 50 / TCF 50 Steel holed platform applicable to wire shelf for TCN 50 / TCF 50	\$3.380,00	\$3.380,00
4	1	Pc	SPECTROPHOTOMETER UV-VIS MODEL XD7500, LOVIBOND PN 71307500	\$15.640,00	\$15.640,00

			Include: 4 batteries (AA) 1 power cord 4 round buckets with lids and 1 blank cuvette XD 7x00 (ø 24 mm) 1 blank cuvette (ø 16 mm) for XD 7000/XD 7500 Quick start guide in 24 languages Instruction manual in 8 languages		
5	1	Pc	MOISTURE BALANCE MODEL MB27, OHAUS PN 30251683 Maximum capacity of 90 g. Readability moisture content of 1 mg/0.01%. 3.5" pan size Temperature range 50°C – 160°C Delivers reliable and accurate results for a wide variety of moisture analysis applications. Applications include percent moisture determination, percent solids determination, and weighing. Halogen heating and dual weight and temperature calibration provide fast, reliable results. User-friendly touch button design for easy operation	\$4.500,00	\$4.500,00
6	1	Pc	ANALYTICAL BALANCE MODEL PR224/E, OHAUS PN PR224/E Capacity 220g Readability 0.1 mg	\$4.770,00	\$4.770,00
7	24	Pc	SPINBAR MAGNETIC STIR BARS OCTAGON, VWR PN 58947-106x12 / 58948-950 Octagon magnetic stirring bars with integral pivot ring are the most commonly used shape. Alnico magnet encapsulated in FDA Grade, USP Class VI Teflon® PTFE low-friction coating; durable and inert Pivot ring aids in reducing friction and chattering (58948-091 does not have a pivot ring) Autoclavable Manufactured in a registered ISO 9001:2008, as verified by SGS certification Interrupted profile provides greater surface area and added turbulence when compared to the smooth surface of cylindrical bars. 12 PC LENGTH 22 MM (7/8") DIAMETER 7.9 MM (5/16") 12 PC LENGTH 28 MM (1 1/8") DIAMETER 7.9 MM (5/16")	\$22,00	\$528,00
8	240	Kg	NO BID	-	-
9	1	Pc	AUTOMATIC REFRACTOMETER ABBEMAT 3000, ANTON PAAR PN 153451 For measuring the concentration and refractive index of liquids and pastes, the Abbemat 3X00 refractometers embody reliability, precision, and convenience. These benchtop refractometers offer you an exceptional combination of technical expertise and user-friendly operation. They are not affected by environmental conditions and require minimal cleaning and no maintenance. The premium technology and compactness of the Abbemat 3X00 refractometers transform time-consuming measurements into highly efficient quality control. Choose from three instruments designed to satisfy the requirements of your field of application and budget. -For routine sugar and beverage analysis -Available sugar scales, e.g. Brix, saccharose, HFCS scales -Results within 4 seconds with temperature-corrected measurements	\$9.729,00	\$9.729,00

10	2	Pc	RELIABLE OVERHEAD STIRRERS MODEL ACHIEVER 5000, OHAUS PN e-A51ST020 Maximum viscosity of 10,000 mPa.s Maximum torque of 20 Ncm Stirring speed range 30-2000 rpm Stirring volume up to 25 l (H ₂ O) Bright LED digital display for speed, real-time torque trend LED indicator bar and built-in timer Sealed aluminum housing with IP54 ingress protection rating Keyless chuck for simple one-handed operation Brushless motor for quiet operation and main power switch Simple knob control, lock button to prevent unintentional setting changes, and full protection for overload, overtemperature, and overcurrent conditions Does not include accessories such as support, double clamps and chains. These accessories are sold separately.	\$2.270,00	\$4.540,00
11	2	Pc	PORTAVO 904 PH MODEL PHMETER KIT WITH SE102-MS ELECTRODE, CA/MS-001XFB-L CABLE, ZU0934 STORAGE CASE, USB CABLE AND CS-PSET479 CALIBRATION BUFFERS SET, KNICK PN 904SET-PH Include Cole-Parmer electrode base support EW-98766-24	\$2.815,00	\$5.630,00
12	1	Pc	KIT PHOSPHATE HR L TEST 5 TO 80 MG/L PO₄, LOVIBOND PN 56L027865x1/ 56L013565x1/ 56L014465x1/ 56P096240x1/ 56R019090x1 Kit includes: KS278-Sulphuric Acid 50 % V/V 65 mL Acidity / Alkalinity P Indicator PA1 65 mL Hardness Calcium Buffer CH2 65 mL 5 KP962-Ammonium Persulphate Powder Powder / 40 g Phosphate HR, Ortho Reagent Set 1 pc.	\$209,00	\$209,00
13	1	Pc	SILICATE HR PP TEST 1 TO 90 MG/L SiO₂ POWDER, LOVIBOND PN 535700 Silica HR Reagent, Set F10 – 100 TEST	\$221,00	\$221,00
14	1	Pc	MERIT WATER STILL MODEL W4000/EURO 220V, STUART PN W4000/EURO Output: 4 litres/hr, single distilled Ph: 5.0 – 6.5 Conductivity, µS/cm-1: 3.0 – 4.0 Resistivity, mOhm-cm: 0.25 – 0.3 Temperature: 25 - 35°C Pyrogen content: Pyrogen free Water supply: 1 litre/min / 3 – 100psi (20-700kPa) Electricity supply 220 or 240V, 50-60Hz Power requirement: 3kW Dimensions, mm (w x d x h): 500 x 150 x 450 IP Rating: 31	\$4.404,00	\$4.404,00
15	2	Pc	GUARDIAN™ 5000 HOTPLATES & STIRRERS, OHAUS PN e-G51HS07C Hot Plate and Stirrer with Ceramic Lid (7 x 7 inches) - Catalog Number 15 liter capacity Backlit LCD display for temperature and speed with green indicator lights when the unit is heating and stirring Featured hot top indicator light, probe in use icon, and single point calibration icon Stirring speed from 60 to 1600 rpm. Ambient temperature range +5°C to 500°C (ceramic lid) SmartHousing stays cool to the touch and is chemical resistant (IP21 ingress protection) Polycarbonate front panel, control knobs, on/off switch for heater disconnection Audible alarm and Safety/Heat protection shut down the heater in the event of a	\$1.400,00	\$2.800,00



INDUSTRIAL BUSINESS INTL CORP

1580 Sawgrass Corporate Parkway
Suite 130, Sunrise, FL 33323
Tel: 954-302-3187, 315-4781
Fax: 954-838-7746
E-mail: ibicorp@intech-ie.com

			malfunction. Temperature calibration function for 3 probe set points and 3 plates		
16	1	Pc	NO BID	-	-
17	1	Pc	SPECTROPHOTOMETER UV-VIS MODEL XD7500, LOVIBOND PN 71307500 Include: 4 batteries (AA) 1 power cord 4 round buckets with lids and 1 blank cuvette XD 7x00 (ø 24 mm) 1 blank cuvette (ø 16 mm) for XD 7000/XD 7500 Quick start guide in 24 languages Instruction manual in 8 languages	\$15.640,00	\$15.640,00
			Delivery Time Items 1,5,6,7,8,9,10,14,15: 4-7 weeks after receipt of order and payment (subject to changes) Items 3,4,11,12,13,17: 8-14 weeks after receipt of order and payment (subject to changes) The delivery time of the items offered is subject to changes generated by events outside the company's control, such as: 1. Climatic phenomena that do not allow the transport of raw material to the factory, local transport abroad of the manufactured material and/or international transport of the product. 2. Normal functioning of Venezuelan and/or foreign customs. 3. Disruption of public order in the country of origin, country of transit and/or final country. 4. Criminal and/or terrorist acts. 5. Any other event considered major force. Payment terms Prepayment with PO Volume & Weight Weight / Volume to be advised		

**PLEASE TRANSFER TO OUR
ACCOUNT AT:**

Branch Banking & Trust Co.
450 North Pine Island
Plantation, FL 33324
Account #: 0140953040
ABA# 053-101-121
Routing/Transit Number: 2631-9138-7
Swift Code: BRBTUS33

THANK YOU FOR YOUR BUSINESS

Subtotal	US \$	109,761.00
Freight	US \$	Included
Insurance	US \$	Included
Docs.	US \$	Included
TOTAL	US \$	109,761.00